

INTERIOR FURNISHING WORK

SL. NO.	ITEM DESCRIPTION	UNIT	QTY.	RATE (Rs.)	AMOUNT (Rs.)
1	<u>Flooring</u>				
a)	Providing and laying of 2' x 2' Vitrified tile flooring of approved make and shade viz. RAK (IMP - OFGY) or EURO (ATHENA) over necessary levelling screed of 1 : 4 cement mortar (20 mm thick) with proper slope wherever required including pointing of the joints with white cements and matching pigments, curing etc. complete in all respects (excluding Toilets and non customer area).	Sft.	1390.00		
b)	Providing, laying and fixing 7.5 mm thick Ceramic Tiles of Kajaria make and shade, design grade (iv) printed colour over necessary levelling screed with sand cement mortar (1 : 4) in flooring. Joint will be finished neatly with white cement paste pigment to match the colour of tiles etc. Toilet area : Floor (300 x 300 mm.)	Sft.	160.00		
c)	Providing and laying mirror polished granite slab of approved shade, quality and thickness to floor and steps at all levels and heights fixed to the existing floor with " Fevimate " of Pidilite or similar approved chemical adhesive of adequate thickness to suit the required level including preparing the existing surface, as necessary, with supply requisite materials including finishing the joints with pigment admixed with white cement, all complete as Basic rate of granite shall be approx. Rs. 2250.00 per Sqm.	Sft	80.00		
d)	Providing and laying 25mm thick Kota stone slab at treads and risers of entrance steps over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and polishing complete. Rates to include cost of teaking out existing flooring and removal of debris out side the premises in conformity with Municipal regulation.	Sft.	85.00		
e)	Providing and laying glazed ceramic tiles of approved size and in combination of approved shades of textured design, Kajaria - Plus or similar approved equivalent to dado of toilets at all levels and heights over minimum 12mm thick cement plaster 1:3 (1 cement : 3 sand) as bed mortar including laying and finishing joints with white cement slurry mixed with pigment to match the shade of tiles, as directed.	Sft.	310.00		
2a)	Providing and fixing in position false ceiling in Gypboard 12 mm thick for horizontals & verticals fixed over G.I framework as specified by India Gypsum Co. Ltd including trap doors for A.C unit in 18 mm thick M.R garde Plywood with Stainless Steel hinges & locks with moulding 1" x 1" for edges including finishing with White Plastic Emulsion Paint etc. complete in all respects. (Only plan area will be measured for payment. No extra payment will be made for cutouts, grooves, mouldings etc.)	Sft	525.00		
b)	Providing and fixing in position false ceiling in Armstrong 600 x 600 mm x 15/16 mm Dune Supreme RH 99 Prima tile with Tegular edge framework as specified by Armstrong Co. with suspenders wherever required. Making necessary framework for A.C ducting, if any, and necessary cutouts for diffusers and light fittings, taping and finishing to proper line & level, including making grooves and trap doors for A.C unit in 18 mm thick M.R Grade Plywood with Stainless Steel hinges & locks with moulding 1" x 1" for edges including finishing with White Plastic Emulsion Paint etc. complete in all respects.				

CARRIED OVER :

SL. NO.	ITEM DESCRIPTION	UNIT	QTY.	RATE (Rs.)	AMOUNT (Rs.)
---------	------------------	------	------	------------	--------------

BROUGHT FORWARD :

	(Only plan area will be measured for payment. No extra payment will be made for cutouts, grooves, mouldings etc.)	Sft	350.00		
c)	Providing and fixing polished 1st class teak wood moulding (out of 50 x 50 mm sections) at junctions of false ceiling , walls and at other locations including melamine finish.	Rft.	230.00		
3	<u>Entrance Door</u>				
a)	Providing and fixing Entrance Door (glazed) as per drawing no. 11 in silver Anodised aluminium door section (jindal make) in top and bottom, glazed with 12 mm thick glass of approved make with etching and frosting. Item to include floor springs, lock, all necessary hardware of stainless steel finish as approved by the Project Consultant/Bank. Complete in all respect.	Sft.	26.00		
b)	<u>Sliding glazed Door</u> Providing and fixing glazed sliding Door as per drawing in silver Anodised aluminium door section (jindal make) in top and bottom, glazed with 8 mm thick glass of approved make with etching and frosting. Item to include necessary hardware for sliding movement of door viz. Pullys, tees etc, lock, all necessary hardware of stainless steel finish as approved by the Project Consultant/Bank. Complete in all respect.	Sft.	11.00		
4	<u>Front Office Counter :</u>				
	Providing and fixing in position Front Office Counter 2' - 6" wide as per drawing No. (1 - A, 1 - B, 1 - C, 1 - D and 15) comprising of the following complete in all respects :				
i)	Working top made with 25 mm thick plywood finished with 1 mm thick laminate. Outside edge of the working top shall be provided with 1 1/4" x 1" teak wood moulding finished with melamine polish. Inside edge will be provided with 1/2" x 1" teak wood beading patti with melamine finish.				
ii)	Vertical fascia (Apron) made with 18 mm thick plywood finished with 1 mm thick laminate with 1 mm thick groove at the joint of laminates of two different shades.				
iii)	Vertical drop (horizontal band) shall provided on the fascia below the working top made with 18 mm thick plywood finished with 1 mm thick groove shall be provided at the joint of two different shades of laminate.				
iv)	Glazed Partition above working top to be provided with 12 mm thick clear glass cut to the standard shape fixed to partition as per fixing details and to boxing with concealed S.S finished "D" brackets as shown in the drawing. The exposed edges of the glass shall be finished in mirror polish.				
v)	3' - 10" high Boxing (10" x 10") made with 18 mm thick plywood finished with 1 mm thick laminate including providing and fixing 6 mm thick square frosted glass at a height 3' - 2" above finished floor level.				
vi)	1' - 9" high Boxing (5" x 5") made with 12 mm thick plywood finished with 1 mm thick laminate.				

SL. NO.	ITEM DESCRIPTION	UNIT	QTY.	RATE (Rs.)	AMOUNT (Rs.)
---------	------------------	------	------	------------	--------------

BROUGHT FORWARD :

- vii) Vertical support made with 18 mm thick plywood finished with white enamel paint.
- viii) Telescopic CPU Stand/ready made/keyboard tray shall be provided of approved model and make.
- ix) Footrest made with teak wood member of size 4" x 1½ " finished with French polish.
- x) Drawer units as per drawing shall be provided with multipurpose Godrej locks in each drawer. Facia of drawer unit shall be finished with 1 mm thick laminate and all other sides shall be finished with white enamel paint. The drawers will be provided with handles (stainless steel finish) and channels as per approval of the project Consultant/Bank.
- xi) Boxing as per drawing made with 12 mm thick plywood finished with synthetic enamel paint shall be provided below the table top for electrical conducting and at the bottom for the LAN cabling/telephone wire conducting.
The item to include all necessary hardware and fittings in stainless steel finish, lipping to all edges and making provision only for electrical fitting behind the front. Vertical drop and also in the 10" x 10" boxing as shown in the drawing. Necessary beadings with melamine polish for fixing the glass are to be provided.

Rft. 8.50

5 Cash Counter :

Providing and fixing in position cash counter 2' - 9" wide as per drawing no. (2 - A, B, C, D, E, F) comprising of the following :

- i) Working top made with 25 mm thick plywood finished with 1 mm thick laminate. Outside edge of the working top shall be provided with 1¼" x 1" teak wood moulding finished with melamine polish. Inside edge will be provided with ½" x 1" teak wood beading patti wiht melamine polish.
- ii) Vertical facia (Apron) made with 18 mm thick plywood finished with 1 mm thick laminate with groove at the joint of laminates of laminates of two different shades.
- iii) Vertical drop (horizontal band) shall provided on the facia below the working top made with 1 mm thick laminate with provision for concealed light, 1 mm thick groove shall be provided at the joint of two different shades of .
- iv) Glazed partition of 1' - 4" height above working top provided with 12 mm thick toughened and frosted glass besides non - transparent film from inside fixed to partition as per fixing details and to boxing with concealed S.S finished 'D' brackets as shown in the drawing. The exposed edges of the glass shall be finished in mirror polish.

CARRIED OVER :

SCH-INT/3

41

BANK OF INDIA -CHANDANNAGORE
DE SARKAR & ASSOCIATES

SL. NO.	ITEM DESCRIPTION	UNIT	QTY.	RATE (Rs.)	AMOUNT (Rs.)
---------	------------------	------	------	------------	--------------

BROUGHT FORWARD :

- v) Transaction top shall be provided with 12 mm thick toughed glass (Partly glazed partly frosted) fixed horizontally with concealed Stainless Steel D bracket. Both exposed edges (inside & outside) shall be moulded and finished in mirror polish.
- vi) Glazed partition having height 1' - 0" above the transaction top (in facia) shall be provided with 12 mm thick glass (clear) with cutout of 8" x 4" as per drawing. The edges of cutout and the top edge of glass are to be mirror polished and to be fixed to partition as per fixing details and to boxing with concealed S.S finished "D" bracket as shown in glass (clear) above the silt to be fixed to partition as per fixing detail and to boxing with concealed S.S finished "D" brackets as shown in drawing. The exposed edges shall be finished in mirror polish.
- vii) 7' - 7" high Boxing (10" x 10") made with 18 mm thick plywood as per drawing with 1' - 6" horizontal extension at the top including providing and fixing 6 mm thick square frosted glass at a height of 5" - 11" above finished floor level.
- viii) 1' - 9" high Boxing (5" x 5") made with 12 mm thick plywood finished with 1 mm thick laminate are to be provided.
- ix) Telescopic CPU Stand/ready made keyboard tray shall be provided of approved model and make.
- x) Foot rest made with teak wood member of size 4" x 1½" finished with french polish.
- xi) Drawer unit as per drawing shall be provided and each drawer should have vertical partitions for keeping the currency notes and multipurpose Godrej locks. Facia of drawer unit shall be finished with 1 mm thick laminate and all other sides shall be finished with white enamel paint. The drawers will be provided with handles (Stainless Steel finish) and channels as per approval of the project Consultant/Bank.
- xii) Boxing as per drawing made with 12 mm thick plywood finished with Synthetic enamel paint shall be provided below the top for electrical conduiting and at the bottom for the LAN cabling/Telephone wire conduiting. The item to include all necessary hardware and fitting in stainless steel finish lipping to all edges and making provision only for electrical fitting behind the vertical drop and also in the 10" x 10" boxing as shown in the Necessary beadings with matching melamine polish for fixing the glass are to be provided as per drawing/ as per directed.

Rft. 8.50

6 Solid Full Height Partition

Providing and fixing in position Solid Full height Partition in frame work including door in 2' x 2' grid (horizontally and vertically) comprising of 2" x 1½" teak wood.

Section with 6 mm thick plywood on both sides finished with 1 mm thick laminates of approved make and colour as shown in drawing no. 17 item to include 2" x 2" teak wood member for doorframe.

CARRIED OVER :

SCH-INT/4

42

BANK OF INDIA -CHANDANNAGORE
DE SARKAR & ASSOCIATES

SL. NO.	ITEM DESCRIPTION	UNIT	QTY.	RATE (Rs.)	AMOUNT (Rs.)
---------	------------------	------	------	------------	--------------

BROUGHT FORWARD :

- 6 Contd..
All exposed teak wood surfaces to be finished in melamine polish of matching laminate colour as directed including all necessary Stainless Steel finish fittings/hardware, door closers, Godrej locks and wood preservative paint etc. as per list of approved material and as approved by the Project Consultant in all respects. (In case of False ceiling, the vertical teak wood members to be fixed with pucca ceiling but the area of partition payable will be below the false ceiling only).
- Sft. 17.00
- 7 Partly Glazed Full Height Partition
Providing and fixing in position partly glazed Full Height Partition work as shown in the drawing nos. 3 & 4 including door as shown in drawing no. 13 in frame work at 2' x 2' grid (horizontally and vertically) comprising of 2" x 1 1/2" teak wood section and or as per frame work shown in the drawing with 6 mm plywood on both sides finished with 1 mm thick laminates of approved shade and colour as shown in drawings.
Item to include 8 mm thick glass with etching and frosting as per design and 2" x 2" teak wood member door for sides and glass sides and teak wood doorframe to take 8 mm thick glass with etching and frosting.
All exposed teak wood surfaces to be finished in melamine polish of matching laminate colour as directed including all necessary Stainless Steel finish fittings/hardware, door closers, Godrej locks and wood preservative paint etc. as per list of approved material and as approved by the Project Consultant/Bank complete in all respects.
(Note : In case of False ceiling, the vertical teak wood member to be fixed with pucca ceiling but the are of partition payable will be below the false ceiling only)
- Sft. 52.00
- 8 Partly Glazed Partition for Cash Cabins
Providing and fixing in position 7' - 7" high partly glazed partition for Cash Cabins as per drawing nos. (2 - A, B, C, D & E) including door drawing no. 12 in frame work at 2' x 2' grid (horizontally and vertically) comprising of 2" x 1 1/2" teak wood section and / or as per frame work shown in the drawings with 6 mm plywood on both sides finished with 1 mm thick laminates of approved shade and colour as shown in drawings. Item to include 8 mm thick glass with etching and frosting as per design and glass with etching and frosting. The door will be provided with teak wood louvers finished in melamine polish of matching laminate colour. The doors are also to be provided with Godrej Night Latch. Two Wooden trays are also being provided as per drawing. Necessary cutouts are to provide in the glass and the edges of the glass cutouts are to be finished in mirror polish.
All exposed teak wood surfaces to be finished in melamine polish of matching laminate colour as directed including all necessary Stainless Steel finish fittings/hardware, door closer, Godrej locks and wood preservative paint etc. as per list of approved material and as approved by the Project Consultant/Bank complete in all respect.
- Sft. 137.00

CARRIED OVER :

SCH-INT/5

43

BANK OF INDIA -CHANDANNAGORE
DE SARKAR & ASSOCIATES

SL. NO.	ITEM DESCRIPTION	UNIT	QTY.	RATE (Rs.)	AMOUNT (Rs.)
---------	------------------	------	------	------------	--------------

BROUGHT FORWARD :

9 Partly Glazed Low Height Partition

Providing and fixing in position partly glazed low height partition (2½" thick) in frame work with teak wood vertical members at 2' center to centre and 3 horizontal members at equal distance comprising of 2" x 1½" teak wood section with 6 mm plywood on both sides finished with 1 mm thick laminates of approved make and shade as shown in drawing no. 14 or 3. Item to include 12 mm thick glass (clear/frosted) to be fixed as shown in drawing. The exposed edges of the glass to be finished in mirror polish. Teak wood runner should be melamine polished in matching colour of laminate etc. complete in all respect.

Sft. 47.00

10 Providing and fixing in position Single skin Full height Partition in frame work including door in 2' x 2' grid (horizontally and vertically) comprising of 2" x 1½" teak wood.

Section with 6 mm thick plywood on one side finished with 1 mm thick laminates of approved make and colour as shown in drawing no. 17. All exposed teak wood surfaces to be finished in melamine polish of matching laminate colour as directed and wood preservative paint etc. as per list of approved material and as approved by the Project Consultant in all respects. (In case of False ceiling, the vertical teak wood members to be fixed with pucca ceiling but the area of partition payable will be below the false ceiling only).

Sft. 20.00

11 Providing and fixing **aluminium composite panel cladding** to building facades conforming to the following specifications :

Aluminium rectangular (50 x 50 mm - approx. 1.10 mm thick) tubular section frame work comprising of horizontal and vertical component at spacings not exceeding 600 mm c/c. firmly fixed to the building face in suitable manner.

4.00 mm thick PVDF coated aluminium composite panel with virgin LDPE core (3.50 mm thick and skin thickness on either side of 0.25 mm of approved shade and fixed to the aluminium frame work by suitable means maintaining uniform grooves. (not less than 4.00 mm wide) at junctions of ACP sheets and duly treated with silicon sealant.)

Sft 122.00

12 Supplying and fixing in position **37 mm thick door shutter** made of 15 mm thick well seasoned second class teak wood planks with double layer (6 mm + 4 mm thick) BWR grade plywood finished with 1.00 mm thick laminate sheet (without joints) of approved quality on both sides of the door shutter upto 900 mm from floor level. The upper portion of the shutter is to be provided with 8 mm thick clear float glass fixed with polished teak wood glazing beads of approved design, complete as per drawing. Rate to include cost of hardware fittings e.g. mortice locks, brass hinges, door handles etc. of approved make and quality. The exposed timber surfaces are to be polished in approved colour and finishing the same with melamine lacquer in mat satin finish.

Sft. 20.00

CARRIED OVER :

SCH-INT/6

44

BANK OF INDIA -CHANDANNAGORE
DE SARKAR & ASSOCIATES

SL. NO.	ITEM DESCRIPTION	UNIT	QTY.	RATE (Rs.)	AMOUNT (Rs.)
---------	------------------	------	------	------------	--------------

BROUGHT FORWARD :

- 13 Providing and fixing **aluminium anodized** (Bronze colour of 15 micron thickness in mat satin finish). glazed windows made from extruded section of 34 series fixed with rawl plugs and screws etc. at all levels including cost of necessary hardware fittings including providing and fixing 5 mm thick clear / obscured float glass panes, gaskets, glazing beads and sealing joints between wall and window with silicon sealants of approved make, provision for fixing glass panes from inside and Neoprene weather seats etc. all complete as per drawing.
- (Rate to include cost of taking out existing steel casement/wooden windows including mending good damages, stacking serviceable materials at site and removal of unserviceable materials outside the campus in conformity with local regulations).
- i) Sliding portion Sft 91.00
ii) Fixed portion Sft 35.00
- 14 Providing and fixing **M.S grills** of required pattern , fixed to steel windows by welding with M.S. flats , square or round bars etc. all complete. Kg 135
- 15 Full Height Storage/Low Height Storage
Providing and fixing in position Full height Storage/Low Height Storage as shown in drawing nos. 8 & 9 respectfully using Plywood of required thickness finished with 1 mm thick laminates as shown in the drawing and all other sides shall be finished with enamel paint as detailed therein.
- The storage units shall be provided with handles (Stainless Steel finish) as per approval of the Project consultant/Bank.
- All exposed plywood surfaces to be finished with 1 mm thick laminate of approval make and shade and all exposed edges of table top and ply vertical to have 1" x 1/4" teak wood lipping. All exposed teak wood sections to be melaminated in matching colour laminate and internal surfaces to have white enamel paint as directed. Item to include plywood boxing, all necessary hardware and fittings in Stainless Steel finish, Godrej multipurpose Locks including magnetic ball catcher etc. complete in all
- Sft. 110.00
- 16 **Stripping off** worn out plaster and raking out joints of walls, ceilings etc. upto any height and in any floor including removing rubbish from the campus in conformity with Local Municipal Regulations. Sft. 285.00
- 17 Providing and laying **brick work of approved quality , laid in cement mortar 1:6** (1 cement : 6 coarse sand) in plain or curved surface including offsets, splays, pillars, piers to small strips etc. at all levels and heights in superstructure complete as per drawing and specification. Cft. 53.00
- 18 **Removal of existing paint** from the plastered surfaces with coir brush, sand paper etc., complete as directed. Sft. 1,930.00

19 Providing and laying in position 1:1.5:3 (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20mm nominal size) **reinforced cement concrete**, including the cost of centering, shuttering, finishing and reinforcement. Cft 35.00

CARRIED OVER :

SCH-INT/7

45

**BANK OF INDIA -CHANDANNAGORE
DE SARKAR & ASSOCIATES**

SL. NO.	ITEM DESCRIPTION	UNIT	QTY.	RATE (Rs.)	AMOUNT (Rs.)
---------	------------------	------	------	------------	--------------

BROUGHT FORWARD :

20 Painting

- | | | | | | |
|------|---|------|----------|--|--|
| i) | Applying two or more coats of Plastic emulsion paint of approved brand over a coat of cement primer after sand preparing cleaning the surface properly. | Sft. | 4,815.00 | | |
| ii) | Applying two coats of synthetic enamel paint of approved brand over a coat of primer in steel and window surface after sand papering cleaning the surface properly. | Sft. | 860.00 | | |
| iii) | White washing with lime –three or more coats to give an even shade. | Sft | 2320.00 | | |

21 Plaster

Plasstering with sand cement mortar (1 : 4) in wall and ceiling where necessary (as directed by Bank authority).	Sft.	305.00
--	------	--------

22 Cement putty

Punning with Plaster of Paris 1.5 mm thick on wall after scraping existing surface to bank area.	Sft.	3,200.00
--	------	----------

23 Blinds

Supplying and fixing in position "MAC" or similar approved vertical blind of approved shade and quality.	Sft.	360.00
---	------	--------

24 **Cleaning the existing glass panes** with spirit including removal of dirt, dust, smoke etc. and ensuring proper fixing, if necessary with matching beads , putty etc.

Sft	251.00
-----	--------

25 Supplying and fixing 4mm thick **best quality clear / obscured float glass** panes setting putty, fitted and fixed with glazing beads including removing the broken glass panes from the existing position, complete as per direction.

Sft.	45.00
------	-------

26 Manager's Table

Providing and fixing in position Manager's Table of size 5' - 6" x 2' - 6" as per drawing no. 6 including side Storage (credenza) by using 25 mm thick plywood for top and 18 mm thick plywood for all other horizontal and vertical members. Telescopic CPU/Stand/readymade Keyboard Tray shall be provided of approved model and make. Footrest made with teak wood member of size 4" x 1½" finished with french polish.

Side storage and back storage (drawing no. 10) as per drawing shall be provided. Facia of side storage (Credenza) shall be finished with 1 mm thick laminate as shown in the drawing and all other sides shall be finished with white enamel paint. The side Storage shall be provided with handles (Stainless Steel finish) and channels as per approval of the Project Consultant/Bank.

All exposed plywood surfaces to be finished with 1 mm thick lamiate of approved make and shade and all exposed edges of table top and ply vertical to have 1" x ¼" teak wood lipping. All exposed teak wood sections to be melaminated and internal surfaces to have white enamel paint as directed. Item to include plywood boxing, all necessary hardware and fittings in Stainless Steel finish, lipping to all edges etc. complete in all respects.

Each 1

CARRIED OVER :

SCH-INT/8

46

**BANK OF INDIA -CHANDANNAGORE
DE SARKAR & ASSOCIATES**

SL. NO.	ITEM DESCRIPTION	UNIT	QTY.	RATE (Rs.)	AMOUNT (Rs.)
---------	------------------	------	------	------------	--------------

BROUGHT FORWARD :

27 Officer's Table :

Providing and fixing in position officer's Table of size 4' - 6" x 2' - 3" as per drawing no. 5 including side storage (credenza) by using 25 mm thick plywood for top and 18 mm thick plywood for all other horizontal and vertical members.

Telescopic CPU/Stand/ready made keyboard Tray shall be provided of approved model and make. Footrest made with teak wood member of size 4" x 1½" finished with French polish. Side storage as per drawing shall be provided. Facia of side storage (credenza) shall be with 1 mm thick laminating as shown in the drawing and all other sides shall be finished with white enamel paint.

The side Storage shall be provided with handles (Stainless Steel finish) and channels as per approval of the Project Consultant / Bank.

All exposed plywood surfaces to be finished with 1 mm thick laminate of approved make and shade and all exposed edges of table top & ply vertical to have 1" x ¼" teak wood lipping. All exposed teak wood sections to be melaminated and internal surfaces to have white enamel paint as directed. Item to include plywood boxing, all necessary hardware and fittings in Stainless Steel finish, lipping to all edges etc. complete in all respects..

Each 3

28 Staff Table

Providing and fixing in position Staff table of size 4' - 3" x 2' - 0" as per drawing no. 5 by using 25 mm thick plywood for top and 18 mm thick plywood for all other horizontal and vertical members. Telescopic CPU Stand/ready - made keyboard tray shall be provided.

Drawer units as per drawing shall be provided with multipurpose Godrej Locks in each drawer. Facia of drawer unit shall be finished with 1 mm thick laminate and all other sides shall be finished with white enamel paint. The drawers will be provided with handles (Stainless Steel finish) and Channels as per approval of the Project Consultant/Bank.

All exposed plywood surfaces to be finished with 1 mm thick laminate of approved make and shade and all exposed edges of table top and ply vertical to have 1" x ¼" teak wood lipping. All exposed teak wood sections to be melaminated and internal surfaces to have white enamel paint as directed. Item to include plywood boxing, all necessary hardware and fittings in Stainless Steel finish, lipping to all edges etc. complete in all respects.

Each 1

29 Cash Counting Table

Providing and fixing cash counting table of size 3' - 3" x 2' - 0" x 2' - 6" high by using 25 mm thick plywood for top and 18 mm thick plywood for all other horizontal and vertical members.

Drawer units as per drawing shall be provided with multipurpose Godrej Locks in each drawer. Facia of drawer unit shall be finished with 1 mm thick laminate and all other sides shall be finished with white enamel paint. The drawers will be provided with handles (Stainless Steel finish) and Channels as per approval of the Project Consultant/Bank.

CARRIED OVER :

SCH-INT/9

47

BANK OF INDIA -CHANDANNAGORE
DE SARKAR & ASSOCIATES

SL. NO.	ITEM DESCRIPTION	UNIT	QTY.	RATE (Rs.)	AMOUNT (Rs.)
---------	------------------	------	------	------------	--------------

BROUGHT FORWARD :

29 Contd..

All exposed plywood surfaces to be finished with 1 mm thick laminate of approved make and shade and all exposed edges of table top and ply vertical to have 1" x 1/4" teak wood lipping. All exposed teak wood sections to be melaminated and internal surfaces to have white enamel paint as directed. Item to include plywood boxing, all necessary hardware and fittings in Stainless Steel finish, lipping to all edges etc. complete in all respects.

Each 1

30 Supplying and erecting wall mounted **Customers' writing ledge** of approx. size 350 x 300 mm made of 12 mm thick machine polished smoke glass supported on decorating wrought iron wall brackets of suitable size and quality with vacuum bush.

Each 1

31 Providing approx. 300 mm wide **customer ledge** made of 19 mm thick BWR blockboard and finished on top with 18 mm thick single piece granite of approved shade and quality including moulding piece, all complete as in drawing. Blockboard at the lower end and at the soffit of top portion shall be finished with 1.00 mm thick laminate sheet of approved shade and quality. Free edges of blockboards/plyboards shall have 6 mm thick polished teak wood lipping. Approx. 150 mm gap to be provided in between the blockboards, which shall be divided in **compartments of suitable size** with 12 mm thick BWR grade plyboard finished with laminate sheet of approved shade and quality,

Mtr. 1.00

32 Providing and fixing in position **notice board** as per drawing and conforming to the following specifications

basic frame work :

well seasoned Malayasian sal wood sections, treated with two coats of wood preservatives, minimum 50 x 25 mm, at suitable horizontal / vertical spacings not exceeding 600 mm c/c.

skin membrane :

1 x 4 mm. thick BWR grade plywood over which 12 mm thick approved quality soft board clad with fabric of approved shade and quality.

edge moulding :

All free edges shall have polished 2nd class teak wood moulds of approved shape (finished 50 x 25 mm sections) with melamine lacquer in mat finish.

Front face of the notice board is to be provided with 4 mm thick glazed shutter with locking facility over suitable supporting frame work made of 19 mm thick polished 1st class teak wood : the glass to be fixed with continuous polished 1st class teak wood glazing beads of approved shape all round, all complete as per specifications and instructions.

Sft. 20.00

- 33 Supplying **corner table** of approx. size 1100 mm long x 700 mm deep x 400 mm high, the top of the table is to be provided with 12 mm thick smoke glass supported on C.P.M.S. tubular frame work. All the edges of glass top are to be pencil rounded machine polished, all complete as in drawing.

Each 2

TOTAL

712.34 0.00

106.90 0.00

